



UNIFIX ECO

RIGID ACRYLIC MOUNTING ADHESIVE



TECHNICAL DATA SHEET UPDATED 19/02/2026

Product Information

Single-component, solvent-free, rigid-setting acrylic adhesive. Specifically formulated for structural bonding in the construction sector, it is ideal for bonding thermal and acoustic insulating materials, tiles, ceramics, cork, and skirting boards. Suitable for both professional use and DIY applications.

- + Solvent-free
- + Sandable and paintable once dry
- + High initial tack (suction effect)
- + No mechanical fixing required (no nails)
- + Low VOC content

Recommended Uses

- Structural bonding in construction
- Fixing of wooden, PVC, and ceramic skirting boards
- Installation of tiles, ceramics, and polyurethane elements
- Bonding of cork panels and thermal/acoustic insulating materials
- Domestic and hobby applications

Coverage

- Up to 20 linear meters per cartridge (standard bead diameter)
- 200–300 g/m² when applied with a trowel

Application Instructions

Substrate Preparation

Surfaces must be dry, sound, absorbent, and free from dust, oils, or paint residues. Any surface irregularities must be filled with GLASTER – super lightweight filler.

Product Preparation

The product is ready to use. When supplied in cartridges, cut the seal and apply using a professional caulking gun.

Product Application

Apply the adhesive to one of the surfaces to be bonded, distributing it in continuous beads or dots (for cartridge application) or with a trowel (for pail application), ensuring uniform coverage of the bonding area.

Join the surfaces and apply even pressure to promote adhesion. The adhesive provides high initial tack (suction effect), while final bonding strength is achieved within 48–72 hours.

Cleaning

Clean tools with water while the product is still fresh. Once cured, residues must be removed mechanically.



UNIFIX ECO

RIGID ACRYLIC MOUNTING ADHESIVE



TECHNICAL DATA SHEET UPDATED 19/02/2026

| Packaging | PRODUCT CODE | WEIGHT | UNIT | PACKAGING | PCS/BOX |
|-----------|--------------|--------|------|-----------|---------|
| | 30012 | 300 | ml | Cartridge | 24 |
| | 30014 | 1 | kg | Jar | 24 |
| | 30015 | 6 | kg | Bucket | 1 |
| | 30016 | 13 | kg | Bucket | 1 |
| | 30017 | 20 | kg | Bucket | 1 |

| Technical Data | | |
|-------------------------|--|----------------|
| Base | | Acrylic |
| Physical appearance | | White paste |
| Solids content | | Approx. 75% |
| Customs code | | 3506 9100 |
| Application temperature | | +10°C to +35°C |
| Waiting time | | None |
| Open time | | 30–40 minutes |
| Final setting time | | 48–72 hours |

Warnings

- Do not use at temperatures below +3°C.
- Recommended application temperature range: +10°C to +35°C.

Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. Store in a dry place, away from heat sources and direct sunlight.

Final note

Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations. The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users must



UNIFIX ECO

RIGID ACRYLIC MOUNTING
ADHESIVE



TECHNICAL DATA SHEET UPDATED 19/02/2026

assess whether the product is suitable for the intended application and
assume full responsibility for its use.
