



UNIFIX PRO

ACRYLIC MOUNTING ADHESIVE –
ELASTIC AND VERSATILE



TECHNICAL DATA SHEET UPDATED 19/02/2026

Product Information

Single-component, solvent-free, elastic acrylic adhesive, designed for structural bonding in construction and for applications on thermal and acoustic insulating materials, decorative panels, skirting boards, and drywall. It provides high initial tack, low shrinkage, and excellent elasticity. Also suitable for DIY applications.

- + Solvent-free
- + High initial tack with suction effect
- + Elastic adhesive with low shrinkage
- + Does not crack or shrink
- + Paintable
- + No mechanical fixing required (no nails)

Recommended Uses

- Structural bonding in construction
- Fixing of wooden and ceramic skirting boards
- Installation of wall tiles and ceramics
- Mounting of polystyrene and polyurethane panels, cornices, and ceiling roses
- Application of cork and thermal/acoustic insulating materials
- Domestic and hobby applications
- Sealing of drywall elements

Coverage

- Up to 20 linear meters per cartridge (standard bead diameter)
- 100–300 g/m² when applied with a trowel

Application Instructions

Substrate Preparation

Surfaces must be dry, sound, absorbent, and free from dust, oils, or paint residues. Any surface irregularities must be filled with GLASTER – super lightweight filler.

Product Preparation

The product is ready to use. When supplied in cartridges, cut the seal and apply using a professional caulking gun.

Product Application

Apply the adhesive to one of the surfaces to be bonded, distributing it in continuous beads or dots (for cartridge application) or with a trowel (for pail application), ensuring uniform coverage of the bonding area.

Join the surfaces and apply even pressure to promote adhesion. The adhesive provides high initial tack (suction effect), while final bonding strength is achieved within 48–72 hours.



UNIFIX PRO



ACRYLIC MOUNTING ADHESIVE –
ELASTIC AND VERSATILE

TECHNICAL DATA SHEET UPDATED 19/02/2026

Cleaning

Clean tools with water while the product is still fresh. Once cured, residues must be removed mechanically.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	30018	300	ml	Cartridge	24
	30020	1	kg	Jar	24
	30021	6	kg	Bucket	1
	30022	13	kg	Bucket	1
	30023	20	kg	Bucket	1

Technical Data

Base	Acrylic
Physical appearance	White paste
Solids content	Approx. 80%
Customs code	3506 9100
Application temperature	+10°C to +35°C
Waiting time	None
Open time	30–40 minutes
Final setting time	48–72 hours

Warnings

- Do not use at temperatures below +3°C.
- Recommended application temperature range: +10°C to +35°C.

Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. Store in a dry place, away from heat sources and direct sunlight.



UNIFIX PRO

ACRYLIC MOUNTING ADHESIVE –
ELASTIC AND VERSATILE



TECHNICAL DATA SHEET UPDATED 19/02/2026

Final note

Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations. The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users must assess whether the product is suitable for the intended application and assume full responsibility for its use.
