



# VICEVERSA DIAMOND



STRUCTURAL AND VERSATILE  
SILANE-MODIFIED POLYMER  
ADHESIVE

TECHNICAL DATA SHEET UPDATED 19/02/2026

---

## Product Information

Single-component adhesive and sealant based on modified silane polymers, solvent-free and characterised by moisture-curing (humidity-reactive curing). Specifically designed for structural bonding applications, including outdoor use, it ensures excellent adhesion on both absorbent and non-absorbent substrates. Provides excellent elasticity, low shrinkage, and strong initial tack.

- + Solvent-free
- + Low elastic modulus
- + High initial tack
- + Low shrinkage
- + Low VOC emissions

---

## Recommended Uses

- Structural bonding in construction
- Sheet metal works: flashings and gutters
- Expansion joints between concrete elements
- Bonding of polyurethane and polystyrene, including outdoor applications
- Fixing on non-absorbent substrates (glass, metal, plastic) in indoor and outdoor environments
- Applications requiring a strong suction (initial grab) effect

---

## Coverage

Approximately 15 linear meters per cartridge (standard bead diameter).

---

## Application Instructions

### Substrate Preparation

Surfaces must be dry, sound, absorbent, and free from dust, oils, or paint residues. Any surface irregularities must be filled with GLASTER – super lightweight filler.

---

### Product Preparation

The product is ready to use. Cut the seal and apply using a professional caulking gun.

---

### Product Application

Apply the adhesive in beads or dots to ensure uniform coverage of the bonding area. Join the surfaces and apply constant pressure. Adhesive performance is ensured by ambient moisture, providing immediate initial tack and complete curing within 48–72 hours.

---

### Cleaning

Clean with nitro thinner immediately after use. Once cured, the product can only be removed mechanically.



# VICEVERSA DIAMOND



STRUCTURAL AND VERSATILE  
SILANE-MODIFIED POLYMER  
ADHESIVE

TECHNICAL DATA SHEET UPDATED 19/02/2026

Packaging	PRODUCT CODE	COLOR	WEIGHT	UNIT	PACKAGING	PCS/ BOX
	30129B	White	300 ml	Cartridge	24 pcs	24
	30129T	Transparent	300 ml	Cartridge	24 pcs	24

Technical Data		
Base		Modified silane polymers
Physical appearance		Extra white / Transparent
Solids content		Approx. 80%
Customs code		3909 5090
Application temperature		+10°C to +35°C
Waiting time		None
Open time		30–40 minutes
Final setting time		48–72 hours

## Warnings

- Do not use at temperatures below +3°C.
- Recommended application temperature range: +10°C to +35°C.

## Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 12 months from the production date. Store in a dry place, away from heat sources and direct sunlight.

## Final note

Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations. The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users must assess whether the product is suitable for the intended application and assume full responsibility for its use.



# VICEVERSA DIAMOND

---

STRUCTURAL AND VERSATILE  
SILANE-MODIFIED POLYMER  
ADHESIVE



TECHNICAL DATA SHEET UPDATED 19/02/2026