



VICEVERSA COAT MIRROR



SINGLE-COMPONENT MATT
PROTECTIVE COATING FOR
WALL COVERINGS

UPDATED DATA SHEET 19/02/2026

Product information

Ready-to-use single-component protective coating, developed to protect all types of wall coverings. Once applied, it creates a matt protective barrier that makes wall coverings washable and more resistant to scratches, wear, and dirt. Ideal for both residential and commercial environments.

- + Matt finish
- + Uniform aesthetic appearance
- + Does not alter the colour of the wall covering
- + Non-staining
- + Non-yellowing
- + Solvent-free

Suggested Applications

- Paper wall coverings
- Fiberglass wall coverings
- Non-woven wall coverings (TNT)
- Embossed vinyl wall coverings
- Vinyl or non-woven wall coverings with digital printing

Product yield

- On fiberglass and embossed vinyl: 7–8 m²/kg
- On paper, non-woven, and smooth vinyl: 11–12 m²/kg

Application Guidelines

Substrate preparation

Ensure that the surface to be treated is perfectly dry, clean, and free from The wall covering to be treated with EASY PROTECT must be:

- Completely dry
- Perfectly bonded, free from detachment or bubbles
- Clean, dust-free, grease-free, and dry

Ensure that any adhesive residues have been removed. Wait at least 48 hours after installing the wall covering before applying the protective coating.

Product preparation

Single-component product, ready to use. Shake or mix thoroughly before application to homogenise any sediment.

Product Application

Apply directly onto the wall covering using a closed-cell sponge roller.

One or two coats may be applied, depending on the desired level of protection. Wait at least 1 hour between the first and second coat, or until complete drying.

Do not use on surfaces in direct contact with water or subject to immersion.

ACM Italy S.r.l.

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan), Italy
+39 02 90361148 | info@acm-italy.com

www.acm-italy.com



VICEVERSA COAT MIRROR



SINGLE-COMPONENT MATT
PROTECTIVE COATING FOR
WALL COVERINGS

UPDATED DATA SHEET 19/02/2026

Cleaning

Clean tools with water immediately after use.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS PER BOX
	40148-1	1	kg	Flacone	12

Product Technical Data		
Colour		White (transparent when dry)
Physical appearance		Liquid
pH		7.9
Viscosity		500–700 cps
Solids content		Approx. 30%
Service temperature range		–10°C to +50°C
Minimum application temperature		+5°C
Dust-free at 20°C		30 minutes
Complete drying		48 hours
Customs code		3906 9050

Contraindications

- Substrate and ambient temperature: +10°C to +30°C
- Relative air humidity: max. 75%

Ensure adequate air exchange in the room during and after application to prevent moisture build-up that could interfere with product drying.

Final provisions

Keep out of reach of children and pets.
Dispose of waste in designated construction material containers.

Preservation

The product, in its original unopened packaging and under standard storage conditions (+5°C to +35°C / 41°F to 95°F), is guaranteed for 18 months from the production date.



VICEVERSA COAT MIRROR

SINGLE-COMPONENT MATT
PROTECTIVE COATING FOR
WALL COVERINGS



UPDATED DATA SHEET 19/02/2026

Store in a dry place, away from heat sources and direct sunlight, to preserve product performance and shelf life.

Warnings

The information provided in this Technical Data Sheet is based on our long-standing experience but is intended as a guideline. Therefore, the user must assess whether the product is suitable for their specific application and takes full responsibility for its use.