



VICEVERSA PLASTER

WATERPROOFING COATING FOR WATER PROTECTION



UPDATED DATA SHEET 11/09/2025

Product information

Ready-to-use waterproofing membrane designed for water protection in humid environments, both indoors and outdoors. Ideal for bathrooms, showers, balconies, terraces, and flat roofs, it creates an elastic, durable, and walkable barrier. It offers excellent adhesion and high coverage.

- + High waterproofing performance
- + High yield
- + Low VOC emissions
- + Pedestrian traffic resistance
- + High elasticity

Suggested Applications

- Waterproofing substrates prior to tile installation in bathrooms, showers and humid areas.
- Waterproofing of balconies and terraces.
- Waterproofing of flat roofs.

Product yield

Approx. 1500 g/m² for 1.5 mm thickness.

Application Guidelines

Substrate preparation

Substrates must be dry, absorbent, sound, and clean, free from dust, paint, oil, or other contaminants. Cracks must be sealed using the two-component epoxy adhesive EPOXY ECO. For uneven surfaces, it is recommended to apply powdered cement-based skim coats such as SELF LEVEL FLOORING from the Suprimo line, or ready-to-use skim coats such as TILECOAT. To consolidate and clean the substrate, the use of PRIMER SP is recommended.

Product preparation

Ready to use.
If necessary, dilute with up to 5% clean water.

Product Application

Apply with roller or brush to obtain a uniform thickness of approx. 1.5 mm.

Cleaning

Clean tools with water immediately after use.



VICEVERSA PLASTER

WATERPROOFING COATING FOR WATER PROTECTION



UPDATED DATA SHEET 11/09/2025

Product Technical Data	Base	Acrylic
	Physical appearance	Creamy paste
	Colors	White, grey, red, transparent
	pH	6.5
	Viscosity	2500 cps
	Solid content	Approx. 70%
	Customs code	3506 9100
	Application temperature	+5°C to +40°C
	Drying time	6–8 hours
	Flammability	Non-flammable
Contraindications	Do not apply on non-absorbent substrates. In the case of ceramic tiles, it is recommended to sand the surface to make it porous. Before application, apply one coat of PRIMER AC diluted 1:5. Protect from frost.	
Final provisions	Keep out of reach of children and pets. Dispose of waste in designated construction material containers.	
Preservation	The product, in its original packaging and under standard conditions (+5°C / +35°C 41°F / 95°F), is guaranteed for 24 months from the date of manufacture. It is essential to store it in a dry place, away from sources of heat and direct sunlight, to preserve its properties and shelf life.	
Warnings	The information provided in this Technical Data Sheet is based on our long-standing experience but is intended as a guideline. Therefore, the user must assess whether the product is suitable for their specific application and takes full responsibility for its use.	