



VICEVERSA PLASTER



WATERPROOFING COATING FOR WATER PROTECTION

UPDATED DATA SHEET 19/05/2025

Product information

Ready-to-use waterproofing membrane designed for water protection in humid environments, both indoors and outdoors. Ideal for bathrooms, showers, balconies, terraces, and flat roofs, it creates an elastic, durable, and walkable barrier. It offers excellent adhesion and high coverage.

- + Excellent waterproofing performance
- + High yield and coverage
- + Low VOC content (Volatile Organic Compounds)
- + Walkable surface
- + High elasticity

Suggested Applications

- Waterproofing of substrates prior to tile installation in bathrooms, showers, and humid areas
- Waterproofing of balconies and terraces
- Waterproofing of flat roofs and damp floors

Product yield

Approx. 1000–1500 g/m² in two coats

Application Guidelines

Substrate preparation

Substrates must be dry, absorbent, sound, and clean, free from dust, paint, oil, or other contaminants.

Cracks must be sealed using the two-component epoxy adhesive EPOXY ECO.

For uneven surfaces, it is recommended to apply powdered cement-based skim coats such as SELF LEVEL FLOORING from the Suprimo line, or ready-to-use skim coats such as TILECOAT.

To consolidate and clean the substrate, the use of PRIMER SP is recommended, while in the presence of rising damp, PRIMER PU should be applied.

Product preparation

The product is ready to use. For the first coat, a 5% dilution with water is recommended.

Product Application

Apply with a roller or brush on the surface to be treated. After the first diluted coat, wait approximately 8 hours for complete drying. Then apply a second undiluted coat.

ACM Italy S.r.l.

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan), Italy

+39 02 90361148 | info@acm-italy.com

www.acm-italy.com



VICEVERSA PLASTER



WATERPROOFING COATING FOR WATER PROTECTION

UPDATED DATA SHEET 19/05/2025

Cleaning

Clean tools with water immediately after use.

Product Technical Data

Base	Acrylic
Physical appearance	Creamy paste
Colors	White, grey, red, transparent
pH	6.5
Viscosity	2500 cps
Solid content	Approx. 70%
Customs code	3506 9100
Application temperature	+5°C to +40°C
Drying time	6–8 hours
Flammability	Non-flammable

Contraindications

Do not apply on non-absorbent substrates. In the case of ceramic tiles, it is recommended to sand the surface to make it porous. Before application, apply one coat of PRIMER AC diluted 1:5. Protect from frost.

Final provisions

Keep out of reach of children and pets.
Dispose of waste in designated construction material containers.

Preservation

The product, in its original packaging and under standard conditions (+5°C / +35°C | 41°F / 95°F), is guaranteed for 24 months from the date of manufacture.
It is essential to store it in a dry place, away from sources of heat and direct sunlight, to preserve its properties and shelf life.



VICEVERSA PLASTER

WATERPROOFING COATING
FOR WATER PROTECTION



UPDATED DATA SHEET 19/05/2025

Warnings

The information provided in this Technical Data Sheet is based on our long-standing experience but is intended as a guideline. Therefore, the user must assess whether the product is suitable for their specific application and takes full responsibility for its use.