

VICEVERSA PS PRO

PROFESSIONAL POWDER
ADHESIVE FOR ALL TYPES OF
WALL COVERINGS



TECHNICAL DATA SHEET UPDATED 19/02/2026

Product Information

Professional powder adhesive for all types of wall coverings. It can also be used in combination with all ACM ready-mixed (paste) products.

- + Non-staining
- + Strong initial tack
- + High coverage
- + Ready to use in just 5 minutes
- + Excellent workability
- + Zero VOC (Volatile Organic Compounds)



- Thermal and acoustic insulating wall coverings
- Fiberglass wall coverings
- Vinyl wall coverings with woven or non-woven backing
- Paintable wall coverings
- Heavy wall coverings

Application Instructions

Substrate Preparation

All substrates must be dry, absorbent, sound, and free from dust, paint, or oils. Any cracks or holes must be filled with our lightweight filler GLASTER and, in the case of imperfections, skimmed with a standard gypsum-based filler.


The use of PRIMER AC for consolidation and surface cleaning is always recommended, and PRIMER SP (anti-mould and antibacterial) is advised for damp walls

Product Dilution

Dilute the product with clean water according to the table shown on the packaging.

Product Preparation

1. Stir the water vigorously.
2. Slowly pour the powder into the water while continuing to mix.
3. Wait 3 minutes.
4. Mix again.
5. The product will be ready for use after 5 minutes.



VICEVERSA PS PRO



PROFESSIONAL POWDER
ADHESIVE FOR ALL TYPES OF
WALL COVERINGS

TECHNICAL DATA SHEET UPDATED 19/02/2026

Product Application

Apply the adhesive directly to the back of the wallpaper or onto the wall, according to the wallpaper manufacturer's instructions.

Cleaning


Any excess adhesive at the joints should be removed with a damp sponge.
THE PRODUCT DOES NOT STAIN.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	10166	500	g	Box	24

Technical Data		
Colour		White
Solids content		100%
Customs code		3505 2030
Flammability		Non-flammable
Application temperature		+5°C to +40°C
Waiting time		10–20 minutes
Open time		20–30 minutes
Complete drying		48 hours
Hazard classification		Non-hazardous
Frost resistance		Frost-resistant
Colour		White

Warnings

Do not use on non-absorbent substrates. Do not apply on damp or mouldy walls or on substrates that are not perfectly prepared. Any adhesive spills must be removed immediately with a damp sponge.



VICEVERSA PS PRO

PROFESSIONAL POWDER
ADHESIVE FOR ALL TYPES OF
WALL COVERINGS



TECHNICAL DATA SHEET UPDATED 19/02/2026

Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 60 months from the production date. Store in a dry place, away from heat sources and direct sunlight.

Final note

Keep out of the reach of children and pets.
Dispose of waste in designated containers for construction materials.

Disclaimer

The information in this technical sheet is based on our long-standing experience but is provided as a guideline.

The user is responsible for determining whether the product is suitable for their specific application and for its use.
