

TECHNICAL DATA SHEET

REVISED: 26/05/2022

VICEVERSA UNICLIP

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



Acrylic water-based construction adhesive/mastic, for structural building materials and thermo-acoustic absorbent materials etc. Suction cup effect, strong initial tack. For internal use.

Suitable for:

- Structural construction materials
- Wood, PVC and ceramic baseboard applications
- Tiles and Wall Ceramics applications
- Polystyrene and polyurethane panels, frames and rosettes
- Cork and thermo-acoustic materials

TECHNICAL FEATURES:

- + Solvent free
- + Low shrinkage
- + No nails support required
- + Strong suction cup effect
- + Low VOC (Volatile Organic Compounds)

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust, paints or oils. Any cracks or holes in the wall must be covered with our extra-light filler GLASTER.

ADHESIVE PREPARATION

Mono-component adhesive and ready-to-use.

APPLICATION

Apply the product all over the contact surface.

CONSUMPTION

- About 20 m (linear) per cartridge
- 100-300 g/m² when applied by trowel

CLEANING

Clean the equipment with fresh water immediately after use, or remove mechanically.

CONTRAINDICATIONS

- Do not use at temperatures below +3 °C
- Application is recommended between +10 °C and +35 °C

TECHNICAL DATA SHEET

REVISED: 26/05/2022

VICEVERSA UNICLIP

SPECIAL PRODUCT RANGE FOR BUILDING TRADES AND MATERIALS USED IN CONSTRUCTION



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30035	300	ml	Cartridge	24
30037	700	g	Small Bucket	24
30038	6	kg	Bucket	1
30039	13	kg	Bucket	1
30040	20	kg	Bucket	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 24 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

PRODUCT TECHNICAL DATA

Base	Acrylic
Appearance and colour	White or coloured on request
Solids percentage	about 80%
Customs code	3506 9100
Application temperature	+10°C +35°C
Waiting Time	None
Open Time	About 30-40 min
Setting Time	48/72 hours

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials.

DISCLAIMER

The above mentioned information and prescriptions, even if they correspond to our best experience are purely indicative and must be confirmed by practical applications. Therefore before using, it is necessary to establish if it fits the prescribed use and the final customer assumes any responsibility that may derive from its use.

www.acm-italy.com