



VICEVERSA UNICLIP

SINGLE-COMPONENT WATER-BASED ACRYLIC ADHESIVE FOR STRUCTURAL AND INTERIOR INSTALLATIONS



TECHNICAL DATA SHEET UPDATED 19/02/2026

Product Information

Single-component acrylic adhesive/sealant in water dispersion, formulated for bonding structural elements in construction, skirting boards, insulating materials, and decorative elements.

It ensures strong initial grab with suction effect, low shrinkage, and easy application. Suitable for interior applications.

- + Solvent-free
- + Low shrinkage
- + High initial tack (suction effect)
- + No mechanical fixing required (no nails)
- + Low VOC content

Recommended Uses

- Structural bonding in construction
- Fixing of wooden, ceramic, and PVC skirting boards
- Installation of wall tiles and ceramics
- Mounting of polystyrene and polyurethane panels, cornices, and ceiling roses
- Bonding of cork and thermal/acoustic insulating materials

Coverage

- Approx. 20 linear metres per cartridge (standard bead Ø)
- 100–300 g/m² when applied with a trowel

Application Instructions

Substrate Preparation

Surfaces must be dry, sound, absorbent, and free from dust, oils, or paint residues. Any surface irregularities must be filled with GLASTER – super lightweight filler.

Product Preparation

Single-component product, ready to use.

For cartridge application, cut the seal and apply using a professional caulking gun

Product Application

Apply the adhesive to one of the surfaces to be bonded, distributing it in continuous beads or dots (for cartridge application) or with a trowel (for pail application), ensuring uniform coverage of the bonding area.

Join the surfaces and apply even pressure to promote adhesion. The adhesive provides strong initial tack (suction effect), while final bonding strength is achieved within 48–72 hours.



VICEVERSA UNICLIP

SINGLE-COMPONENT WATER-BASED ACRYLIC ADHESIVE FOR STRUCTURAL AND INTERIOR INSTALLATIONS



TECHNICAL DATA SHEET UPDATED 19/02/2026

Cleaning

Clean tools with water while the product is still fresh. Once cured, residues must be removed mechanically.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	30035	300	ml	Cartridge	24
	30037	1	kg	Jar	24
	30038	6	kg	Bucket	1
	30039	13	kg	Bucket	1
	30040	20	kg	Bucket	1

Technical Data		
Base		Acrylic
Physical appearance		White paste (or coloured on request)
Solids content		Approx. 80%
Customs code		3506 9100
Application temperature		+10°C to +35°C
Waiting time		None
Open time		30–40 minutes
Final setting time		48–72 hours

Warnings

- Do not use at temperatures below +3°C.
- Recommended application temperature range: +10°C to +35°C.

Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24



VICEVERSA UNICLIP

SINGLE-COMPONENT WATER-
BASED ACRYLIC ADHESIVE FOR
STRUCTURAL AND INTERIOR
INSTALLATIONS



TECHNICAL DATA SHEET UPDATED 19/02/2026

months from the production date. Store in a dry place, away from heat sources and direct sunlight.

Final note

Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations. The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users must assess whether the product is suitable for the intended application and assume full responsibility for its use.
