



VK L

VINYL-ETHYLENE ADHESIVE FOR SOLID WOOD PARQUET FLOORING



TECHNICAL DATA SHEET UPDATED 19/02/2026

Product Information

Single-component vinyl-ethylene adhesive in water dispersion, specifically formulated for the installation of solid wood parquet flooring on absorbent substrates and on ceramic surfaces after suitable preparation. It ensures high final bonding strength, good elasticity, low VOC content, and is completely solvent-free.

- + High final bond strength
- + Excellent workability
- + Compatible with underfloor heating systems
- + Low VOC content
- + Solvent-free

Recommended Uses

- Installation of traditional solid wood parquet flooring
- Application on absorbent cementitious screeds
- Installation on ceramic substrates after mechanical abrasion
- Installation on radiant heating systems (heated floors)

Coverage

800–1000 g/m², depending on substrate flatness and type of flooring.

Application Instructions

Substrate Preparation

All substrates must be dry, absorbent, sound, and free from dust, paints, or oils. Any cracks must be sealed using our two-component epoxy adhesive EPOXY.

In the case of uneven surfaces, the application of a cement-based self-leveling compound such as SELF LEVEL FLOORING (Suprimo line) or the ready-to-use skim coat TILECOAT is recommended.

For substrate consolidation and cleaning, the use of PRIMER SP is recommended. In the presence of rising damp or particularly humid substrates, use PRIMER PU.

Product Preparation

The product is ready to use.

Product Application

Apply the adhesive in a single coat using a roller or a No. 2 notched trowel, depending on the substrate and type of flooring.

Roller application

Spread the undiluted product evenly onto the substrate using a short-pile wool roller, treating areas of approx. 10–15 m² at a time. Proceed immediately with flooring installation.

Trowel application

Apply the undiluted adhesive using a No. 2 notched trowel, ensuring uniform distribution. Install the flooring by applying adequate pressure to ensure proper bonding.



VK L

VINYL-ETHYLENE ADHESIVE FOR SOLID WOOD PARQUET FLOORING



TECHNICAL DATA SHEET UPDATED 19/02/2026

Cleaning

Fresh adhesive residues must be removed immediately with a damp sponge. Once cured, removal may require mechanical methods.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	20036-N	6	kg	Bucket	1
	20037-N	13	kg	Bucket	1
	20038-N	20	kg	Bucket	1

Technical Data		
Base		Vinyl-ethylene
Physical appearance		Light brown creamy paste
pH		4.5
Viscosity		100,000 – 150,000 cps
Solids content		Approx. 70%
Customs code		3909 5090
Application temperature		+5°C to +40°C
Waiting time		0 – 20 minutes
Open time		30 – 40 minutes
Complete drying		48 – 72 hours
Minimum sanding time		20 – 30 days

Warnings

- Do not apply at temperatures below +10°C.
- Do not use on damp substrates or surfaces subject to rising damp.
- Non-absorbent substrates must be made porous by sanding or shot blasting.



VK L

VINYL-ETHYLENE ADHESIVE
FOR SOLID WOOD PARQUET
FLOORING



TECHNICAL DATA SHEET UPDATED 19/02/2026

Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. Store in a dry place, away from heat sources and direct sunlight.

Final note

Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations. The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users must assess whether the product is suitable for the intended application and assume full responsibility for its use.
