



# VK M54



## UNIVERSAL LATEX ADHESIVE FOR RESILIENT AND TEXTILE FLOOR COVERINGS

TECHNICAL DATA SHEET UPDATED 19/02/2026

### Product Information

Latex-based adhesive formulated for the rapid installation of commercial carpets, allowing fast foot traffic immediately after installation. Suitable for both direct bonding and double-stick installation methods. It can be used on all types of PVC flooring, cork flooring with PVC backing, and textile floor coverings with polyurethane (PU) foam backing. The adhesive is also compatible with linoleum with natural or synthetic jute backing, as well as materials with Action Back (polypropylene), nylon, or PU backing. It is also suitable for bonding LVT, VCT, and needle-punched carpets, ensuring high performance in both residential and commercial environments.

- + High initial tack
- + Low VOC content
- + High coverage

### Recommended Uses

- PVC and LVT flooring
- VCT and linoleum flooring (with natural or synthetic jute backing)
- Needle-punched flooring and cork flooring with PVC backing
- Commercial carpets (with PU foam, jute, Action Back, nylon, or polypropylene backing)
- Residential carpets with latex foam or sponge rubber backing
- PVC or cork wall coverings

### Coverage

250–350 g/m<sup>2</sup>, depending on the type and condition of the substrate.

### Application Instructions

#### Substrate Preparation

Surfaces must be dry, sound, porous, and completely free from dust, paints, or oily residues. Any cracks or cavities must be properly repaired using the two-component epoxy adhesive EPOXY.

Before installation, it is essential to check the moisture content of the substrate to ensure suitability. The use of PRIMER AC is recommended for substrate consolidation and preparation. In the presence of residual moisture or rising damp, the use of PRIMER SP, specifically designed for surfaces subject to mould and fungi, is recommended.

#### Product Preparation

The product is ready to use and does not require dilution.

#### Product Application

Apply the adhesive in a single coat using a roller or a No. 2 notched trowel, depending on the type of substrate and the material to be installed.

#### Roller application



# VK M54



## UNIVERSAL LATEX ADHESIVE FOR RESILIENT AND TEXTILE FLOOR COVERINGS

TECHNICAL DATA SHEET UPDATED 19/02/2026

Spread the undiluted product evenly directly onto the substrate using a short-pile wool roller, treating areas of approx. 10–15 m<sup>2</sup> at a time. Proceed immediately with the installation of the flooring.

### Trowel application

Apply the undiluted adhesive onto the substrate using a No. 2 notched trowel, ensuring uniform distribution. Install the covering material, applying adequate pressure to ensure proper bonding.

### **Cleaning**

Remove any excess adhesive with a damp sponge before drying.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	20112-N	6	kg	Bucket	1
	20113-N	13	kg	Bucket	1
	20109-N	20	kg	Bucket	1

Technical Data		
Base		SBR latex
Physical appearance		Beige paste
pH		6.8
Viscosity		25,000–35,000 cps
Solids content		Approx. 70%
Customs code		3506 9190
Application temperature		+5°C to +40°C
Waiting time		10–15 minutes
Open time		20–30 minutes
Complete drying		24 hours
Flammability		Non-flammable



## VK M54

---

UNIVERSAL LATEX ADHESIVE  
FOR RESILIENT AND TEXTILE  
FLOOR COVERINGS



TECHNICAL DATA SHEET UPDATED 19/02/2026

---

### Limitations

- Do not use for outdoor applications (use ADHESIVA 2P/G instead)
- Do not apply at temperatures below +3°C
- Do not use on damp substrates or surfaces subject to rising damp
- Treat non-absorbent substrates to make them porous

---

### Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. Store in a dry place, away from heat sources and direct sunlight.

---

### Final note

Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations. The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users must assess whether the product is suitable for the intended application and assume full responsibility for its use.

---