



VK MT4

REMOVABLE WATER-BASED ACRYLIC ADHESIVE



TECHNICAL DATA SHEET UPDATED 19/02/2026

Product Information

Water-based acrylic adhesive specifically formulated for removable applications. Indicated for bonding carpet tiles or rolls, PVC coverings, and needle-punched floor coverings, it provides good initial tack and a long open time.

Its formulation allows removal with cold water, making it ideal for temporary or semi-permanent installations.

- + Long open time
- + Effective initial tack
- + Removable with cold water
- + Low VOC content
- + High coverage

Recommended Uses

- Carpet tiles or rolls
- PVC floor coverings in rolls or tiles
- Needle-punched coverings and carpets with polyurethane (PU) foam backing

Coverage

150–250 g/m², depending on the type and condition of the substrate.

Application Instructions

Substrate Preparation

Surfaces must be dry, sound, porous, and completely free from dust, paints, or oily residues. Any cracks or cavities must be properly repaired using the two-component epoxy adhesive EPOXY.

Before installation, it is essential to check the moisture content of the substrate to ensure suitability. The use of PRIMER AC is recommended for substrate consolidation and preparation. In the presence of residual moisture or rising damp, the use of PRIMER SP, specifically designed for surfaces subject to mould and fungi, is recommended.

Product Preparation

The product is ready to use and does not require dilution.

Product Application

Apply the adhesive directly onto the substrate using a short-pile wool roller, covering approx. 10–15 m² per coat.

Proceed with the installation of the covering according to the recommended method.

Cleaning

Remove fresh adhesive residues with a damp cloth before the product hardens.



VK MT4

REMOVABLE WATER-BASED ACRYLIC ADHESIVE



TECHNICAL DATA SHEET UPDATED 19/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	20153-N	5	kg	Bucket	1
	20154-N-10	10	kg	Bucket	1
	20155-N	15	kg	Bucket	1

Technical Data		
Base	Acrylic	
Physical appearance	Beige liquid	
pH	8.5	
Viscosity	25,000–35,000 cps	
Solids content	Approx. 70%	
Customs code	3506 9190	
Application temperature	+5°C to +40°C	
Waiting time	30 minutes to 5 hours	
Open time	45–60 minutes	
Complete drying	24 hours	
Flammability	Non-flammable	

Limitations

- Do not use for outdoor applications (use ADHESIVA 2P/G instead)
- Do not apply at temperatures below +3°C
- Do not use on damp substrates or surfaces subject to rising damp
- Treat non-absorbent substrates to make them porous

Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. Store in a dry place, away from heat sources and direct sunlight.



VK MT4

REMOVABLE WATER-BASED
ACRYLIC ADHESIVE



TECHNICAL DATA SHEET UPDATED 19/02/2026

Final note

Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations. The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users must assess whether the product is suitable for the intended application and assume full responsibility for its use.
