



VK-P ECO



ACRYLIC-BASED STRUCTURAL ADHESIVE

UPDATED DATA SHEET 13/02/2025

Product information

Acrylic-based structural adhesive is utilized for polystyrene, polyurethane baseboards, and tiles. It provides a strong suction cup effect and excellent initial tack.

- + No highly flammable solvents.
- + Paintable.
- + Strong suction cup effect.
- + No nail support required.

Suggested Applications

- Wood and ceramic baseboard applications
- Tile and wall ceramic applications
- Polystyrene and polyurethane panels, frames, and rosettes
- Cork and thermo-acoustic products materials

Product yield

- Approximately 15 linear meters per cartridge
- 200-300 g/m² when applied with a trowel

Application Guidelines

Surface preparation

All surfaces should be dry, absorbent, strong, and free from dust, paint, or oils. Any cracks or holes in the wall need to be filled with our extra-light filler, GLASTER.

Product preparation

Ready-to-use single-component adhesive.

Cut the cartridge and use a special caulking gun for cartridges.

Product Application

Apply the product to the entire contact surface.

Cleanliness

Immediately clean the equipment with fresh water after use, or remove it mechanically.



VK-P ECO



ACRYLIC-BASED STRUCTURAL ADHESIVE

UPDATED DATA SHEET 13/02/2025

Packs	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS IN BOX
	30024	300	ml	Cartridge	24
	30026	700	gr	Small bucket	24
	30027	6	kg	Bucket	1
	30028	13	kg	Bucket	1
	30029	20	kg	Bucket	1

Product Technical Data	Base	Acrylic
Appearance and color	Extra White or colored on request	
Solids Percentage	Approximately 80%	
Customs code	3506 9100	
Application temperature	+10°C +35°C	
Waiting Time	None	
Open Time	Approximately 30-40 minutes	
Setting Time	48 to 72 hours	

Contraindications

- Avoid using at temperatures below +3 °C.
- It is recommended to apply between +10 °C and +35 °C.

Final provisions

Keep out of the reach of children. Dispose of waste in designated containers for construction materials.

Preservation

The product is guaranteed to remain intact in its original packaging when stored under standard conditions (+5 °C to +35 °C or +41 °F to +95 °F) for 24 months from the date of manufacture. It is essential to keep the product in dry environments, away from heat sources and direct sunlight.

Warnings

The information provided in this Technical Data Sheet is based on our decades of experience, but it is only indicative. Therefore, users must



VK-P ECO

ACRYLIC-BASED STRUCTURAL
ADHESIVE



UPDATED DATA SHEET 13/02/2025

evaluate whether the product is suitable for their specific application and assume responsibility for its use.