

## TECHNICAL DATA SHEET

REVISED: 01/12/2022

# ADHESIVA EASY NON-WOVEN

## POWDER ADHESIVES FOR WALL COVERINGS



Powder-based adhesive for use with non-woven wall covering.

Suitable for:

- All types of wallcoverings
- Vinyl wallcoverings with paper-backing
- Expanded vinyl wallcoverings
- Duplex wallpaper

### TECHNICAL FEATURES

- + Washable after hanging
- + Stainless
- + High yield
- + Zero VOC (Volatile Organic Compounds)
- + Ready to use in 15/20 minutes

### SURFACE PREPARATION

All surfaces must be clean and dry, absorbent and free from dust, paint and oil. Any cracks or holes in the wall must be filled with our light GLASTER filler and, in case of imperfections, smoothed with a normal plaster filler. We recommend using our PRIMER AC primer for preparation and cleaning, and our PRIMER SP (created for resistance to mold and bacteria) where the walls are damp.

### PRODUCT PREPARATION

The product should be diluted in clean water in the proportions as shown in the following table:

#### DILUTION TABLE FOR 200G OF PRODUCT

| WALL COVERING     | DILUTION | m2           |
|-------------------|----------|--------------|
| Fixing            | 10 LT    |              |
| Wallpaper         | 6 LT     | Approx 40-45 |
| Lightweight vinyl | 5 LT     | Approx 35-40 |

1. Stir the water vigorously
2. Tip the contents of the pack of powder into the water, continuing to stir.
3. Leave to settle for 3 minutes
4. Continue to stir
5. After a further 5 minutes the product is ready to be used

# TECHNICAL DATA SHEET

REVISED: 01/12/2022

## ADHESIVA EASY NON-WOVEN

### POWDER ADHESIVES FOR WALL COVERINGS



#### APPLICATION

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

#### CLEANING

It is recommended to wipe off any excess paste from joints and edges using a damp cloth. THIS PRODUCT DOES NOT LEAVE ANY MARKS.

#### CONTRA-INDICATIONS

Do not use this product on a non-absorbent surface, do not apply to damp or moldy walls, or where the surface has not been prepared adequately. Any excess paste on the surface must be wiped off immediately using a damp cloth.

#### PACKAGING

| PRODUCT CODE | WEIGHT | UNIT | TYPE OF PACKAGING | PCS IN BOX |
|--------------|--------|------|-------------------|------------|
| 10164        | 200    | g    | Carton box        | 24         |

#### STORAGE

The product is guaranteed for 60 months from the date of production. IT IS FROST RESISTANT. Store in a dry place.

#### PRODUCT TECHNICAL DATA

|                         |                  |
|-------------------------|------------------|
| Description of Product  | Cellulose Powder |
| Colour                  | white            |
| Percentage of Solids    | 100%             |
| Customs Classification  | 3505 2030        |
| Flame Resistance        | no               |
| Application Temperature | +5°C +40°C       |
| Fixing Time             | 10-20 minutes    |
| Open Time               | 20-30 minutes    |
| Complete Drying Time    | 48 hours         |
| Not Harmful             |                  |
| Frost Resistant         |                  |

#### FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

#### DISCLAIMER

The information contained in the data sheet, based on results of our long experience, are for information only. Therefore, those who intend to use it are required to assess whether the product is suitable for their use, and to assume responsibility for its use.