



ADHESIVA NP

POWDERED ADHESIVE FOR
PAPER WALLCOVERINGS OR
PAPER-BACKED MATERIALS



TECHNICAL DATA SHEET UPDATED 25/07/2025

Product Information

Powder adhesive designed for wallpaper and wallcoverings made of or backed with paper. It can also be combined with all ACM paste adhesives for wallcoverings.

- + Does not stain
- + Strong initial grab
- + High yield
- + Ready to use in just 5 minutes
- + Zero VOC (volatile organic compounds)



- Wallpaper
- Vinyl wallcoverings with paper backing
- Duplex paper
- Expanded vinyl wallcoverings with paper backing (up to 250 g/m²)

Application Instructions

Substrate Preparation

All surfaces must be dry, absorbent, sound, and free from dust, paint, or oil. Any cracks or holes should be filled with our lightweight filler GLASTER, and if needed, skimmed with a standard gypsum-based filler. We recommend using our PRIMER AC for consolidation and cleaning, and PRIMER SP (special anti-mold and antibacterial) for damp walls.

Product Dilution

Dilute the product in clean water according to the ratio shown on the package.

Product Preparation

1. Stir water vigorously.
2. Pour the powder into the water while continuing to stir.
3. Let rest for 3 minutes.
4. Stir again.
5. Ready to use after 5 minutes.

Product Application

Apply the adhesive directly to the back of the wallpaper or to the wall, following the wallpaper manufacturer's instructions.

Cleaning

Clean any excess adhesive from joints with a damp sponge. THE PRODUCT DOES NOT STAIN.



ADHESIVA NP

POWDERED ADHESIVE FOR
PAPER WALLCOVERINGS OR
PAPER-BACKED MATERIALS



TECHNICAL DATA SHEET UPDATED 25/07/2025

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	10001	200	g	Carton	24

Technical Data		
	Physical appearance	Powder
	Color	White
	Solids content	100%
	Customs code	3505 2030
	Flammability	No
	Application temperature	+5 °C to +40 °C
	Waiting time	10–20 minutes
	Open time	20–30 minutes
	Full drying time	48 hours
	Non-toxic	Yes
	Frost-resistant	Yes

Warnings	
	<ul style="list-style-type: none">Do not use the adhesive on non-absorbent substrates.Do not apply on damp or moldy walls or poorly prepared surfaces.Remove any adhesive excess immediately with a damp sponge.

Storage	
	<p>The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 60 months from the production date.</p> <p>It is essential to store the product in a dry place, away from heat sources and direct sunlight.</p>

Final note	
	<p>Keep out of the reach of children and pets.</p> <p>Dispose of waste in designated containers for construction materials.</p>

Disclaimer	
	<p>The information in this technical sheet is based on our long-standing experience but is provided as a guideline.</p>



ADHESIVA NP

POWDERED ADHESIVE FOR
PAPER WALLCOVERINGS OR
PAPER-BACKED MATERIALS



TECHNICAL DATA SHEET UPDATED 25/07/2025

The user is responsible for determining whether the product is suitable for their specific application and for its use.
