

TECHNICAL DATA SHEET

REVISED: 20/03/2023

VICEVERSA SPECIAL 2.0

PROFESSIONAL LINE FOR WALL COVERINGS



Water-based polyurethane polymer adhesive, created for the fixing of flooring in PVC, LVT, and glass fibre wallcoverings in humid areas (bathrooms and saunas for example).

Suitable for:

- Wallcoverings on non-absorbent or low absorbent surfaces
- Vinyl or glass fibre wallcoverings
- Flooring in LVT or PVC
- Application of glass fibre wallcoverings in humid areas (bathrooms and saunas etc)

TECHNICAL FEATURES:

- + Solvent-free
- + Easy to apply
- + Low VOC (volatile organic compounds)

GROUND PREPARATION

All surfaces should be clean, porous (in this case, also non-porous), smooth, free from dust or paint or oil. Any defects should be treated using our light GLASTER filler, or sealant.

PREPARATION OF MATERIALS

Before commencing installation, we suggest leaving the materials on site for one day prior to commencing work for acclimatisation to room temperature. Once SPECIAL 2.0 has been applied to the wall, install the product in accordance with the manufacturer's recommended installation temperature.

PREPARATION OF PRODUCT

SPECIAL 2.0 is a ready to use single component adhesive.

PRODUCT APPLICATION

The product is applied in one coat using a roller.

Apply the product directly onto the wall with a short-pile roller and cover 5/7m² per time. Then hang the wallcovering according to the manufacturers' instructions.

COVERAGE

Coverage depends on the nature of the installation. Yield is approx 200g/m².

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

TECHNICAL DATA SHEET

REVISED: 20/03/2023

VICEVERSA SPECIAL 2.0

PROFESSIONAL LINE FOR WALL COVERINGS



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30042	2,5	kg	Rectangular Bucket	1

PRODUCT TECHNICAL DATA

Base	Polyurethane polymers
Physical appearance	White color
Percentage of solids	Approx 50%
Customs code	3909 5090
Operating temperature	+10°C +35°C
Wait time	None
Open time	Approx 20-30 minutes
Complete drying time	48/72 hours

CLEANING

It is recommended to clean the tools with water immediately after hanging.

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

The information contained in the data sheet, based on results of our long experience, are for information only. Therefore, those who intend to use it are required to assess whether the product is suitable for their use, and to assume responsibility for its use.

www.acm-italy.com