



VICEVERSA SPECIAL 2.0



SINGLE-COMPONENT WATER-BASED POLYURETHANE ADHESIVE FOR WALL COVERINGS. SPECIFIC FOR AREAS IN DIRECT CONTACT WITH WATER

TECHNICAL DATA SHEET UPDATED 19/02/2026

Product Information

Single-component adhesive based on water-dispersed polyurethane polymers, specifically developed for bonding wall coverings and flooring in humid environments or in areas in direct contact with water, such as showers, saunas, and bathrooms.

It is suitable for use on non-absorbent or low-absorbent substrates and ensures excellent adhesion, easy application, and low VOC content.

- + Solvent-free
- + Easy to apply
- + Low VOC content

- Wall coverings on non- or low-absorbent substrates
- Vinyl or fiberglass wall coverings
- LVT and PVC flooring
- Applications in humid environments (bathrooms, saunas, showers, etc.)

Coverage

Approx. 200–250 g/m², depending on the type of substrate and wall covering.

Application Instructions

Substrate Preparation

The substrate must be:

- Dry
- Clean, free from dust, oils, paints, or release agents
- Sound and cohesive

Any cracks or surface imperfections must be repaired using GLASTER – lightweight filler or silicate-based repair materials.

Product preparation

The product is ready to use.

Do not dilute or mix with other products.

If necessary, stir briefly before use to homogenise the consistency.

Product application

Apply the product in a single coat using a short-pile wool roller, covering an area of approx. 5–7 m² at a time (one drop at a time).

Install the wall covering immediately after applying the adhesive, applying light pressure to ensure uniform contact over the entire surface.

Apply at temperatures between +10°C and +35°C.



VICEVERSA SPECIAL 2.0



SINGLE-COMPONENT WATER-BASED POLYURETHANE ADHESIVE FOR WALL COVERINGS. SPECIFIC FOR AREAS IN DIRECT CONTACT WITH WATER

TECHNICAL DATA SHEET UPDATED 19/02/2026

Cleaning

Clean with water immediately after application.
Once cured, the product must be removed mechanically.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	30042	2,5	kg	Rectangular Bucket	2

Technical Data

Base	Polyurethane polymers
Physical appearance	White
Solids content	Approx. 50%
Customs code	3909 5090
Application temperature	+10°C to +35°C
Waiting time	None
Open time	20–30 minutes
Final setting time	48–72 hours

Warnings

- Ambient and substrate temperature: +10°C to +35°C
- Relative humidity: max. 75%

Avoid application below +3°C or on wet surfaces.

Storage

The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 12 months from the production date.

It is essential to store the product in a dry place, away from heat sources and direct sunlight.

Final note

Keep out of the reach of children and pets.
Dispose of waste in designated containers for construction materials.



VICEVERSA SPECIAL 2.0

SINGLE-COMPONENT WATER-BASED POLYURETHANE ADHESIVE FOR WALL COVERINGS. SPECIFIC FOR AREAS IN DIRECT CONTACT WITH WATER



TECHNICAL DATA SHEET UPDATED 19/02/2026

Disclaimer

The information in this technical sheet is based on our long-standing experience but is provided as a guideline.

The user is responsible for determining whether the product is suitable for their specific application and for its use.
