



PRIMER STO-B

WALLCOVERING PRIMER
PIGMENTED | PERMEABLE



DATA SHEET UPDATED 07/10/2026

Product information

Pigmented water-based acrylic primer formulated with special high-coverage technology. It provides excellent coverage with a single coat.

- + Exceptional coverage
- + Easy to apply
- + Water-based and solvent-free
- + High yield
- + Non-flammable
- + Penetrates up to 3 cm into the substrate, helping to consolidate it
- + Very low V.O.C. content

Recommended uses

- Restoring and renovating old walls
- White color makes wall paint application easier

Coverage

Approximately 75 square feet per quart, depending on the porosity of the substrate.

Application instructions

Product preparation

The product is ready to use.

Application

Apply PRIMER STO-B to walls or floors using a roller or brush.

The product dries in approximately 3–4 hours at 68–77°F (20–25°C). Drying time may vary depending on temperature and environmental conditions.

Cleaning

Clean any spills with a damp sponge.

THE PRODUCT DOES NOT STAIN

PRIMER STO-B

WALLCOVERING PRIMER
PIGMENTED | PERMEABLE



DATA SHEET UPDATED 07/10/2026

Technical product data

Base	Water-based acrylic
Appearance and color	Viscous White liquid
pH	7.5-8.5
Viscosity	4000-5000 cps
VOC	<2 µg/m3
Solids Content	50-55 %
Customs code	3209 1000
Application temperature	+41°F-+104°F
Drying Time	3-4 hours
Non-flammable	
Protect from freezing	

Warning

Do not apply to non-absorbent substrates such as glass, ceramic, or laminate surfaces.

Storage

The product is guaranteed for 24 months from the date of production when stored in its original packaging under standard conditions, at temperatures between +41°F and +95°F (+5°C to +35°C).

Store in a dry place, away from heat sources and direct sunlight.

Disclaimer

Keep out of reach of children.

Dispose of leftover product in designated containers for construction materials.

The information contained in this technical data sheet is based on our many years of experience and is provided for guidance only. Users must assess the suitability of the product for the intended application and assume full responsibility for its use.