

## **PRIMER STO-B**

## WHITE - PERMEABLE WALLPAPER PRIMER



## DATA SHEET UPDATED 16/10/2024

Product information	<ul> <li>PIGMENTED water-based acrylic primer, formulated with a special high-coverage technology.</li> <li>It allows for high coverage with a single layer of application.</li> <li>Exceptional coverage</li> <li>Easy to apply</li> <li>Outstanding coverage</li> <li>Water-based, solvent-free</li> <li>High yield</li> <li>Non-flammable</li> <li>Penetrates up to 3 cm into the support consolidating</li> <li>Very Low V.O.C. (Volatile Organic Compounds)</li> </ul>	
Recommended uses	<ul><li>Restoring old wall and renovation old walls.</li><li>The white color makes it easy to apply wall paints.</li></ul>	
Coverage	Approximately 75 square feet per part, depending on the porosity of the substrate.	
Application instructions	<ul> <li>Product preparation The product is ready to use. The product retains high yield. </li> <li>Application Apply PRIMER STO-B to walls or floors with a roller or brush. The product dries in 3/4 hours at 68-77°F (20-25°C). The drying time varies depending on the temperature and nature of the environment. </li> <li>Cleaning Clean possible spills with a damp sponge. THE PRODUCT DOES NOT STAIN</li></ul>	

## **PRIMER STO-B**

WHITE - PERMEABLE
WALLPAPER PRIMER

DATA SHEET UPDATED 16/10/2024

Technical product data	Base	Acrylic water-based
	Appearance and color	Viscous White liquid
	PH	7.5-8.5
	Viscosity	4000-5000 cps
	VOC	<2 µg/m3
	Solids percentage	50-55 %
	Customs code	3209 1000
	Application temperature	+41°F-+104°F
	Drying Time	3/4 hours
	Non-Flammable product	
	Keep free from frost	
Warning	Do not apply to non-absorbent substrates (glass, ceramics, laminates). Protect from frost	
Storage	The product is guaranteed in its original packaging, in standard conditions $+41^{\circ}$ F to $+95^{\circ}$ f (+5 °C to + 35 °C), for 24 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.	
Disclaimer	Keep out of reach of children. Dispose of leftovers in special containers for building materials. The information contained in the data-sheet is the result of our many years of experience but is only indicative. Therefore, those who want to use it are obliged to assess whether the product is suitable for use and take responsibility for its use.	



ACM Italy S.r.I. Viale Enrico Mattei, 8 - 20010 Casorezzo (Milano) +39 02 90361148 | info@acm-italy.com www.acm-italy.com