



PRIMER STO-R

ADHESION PROMOTING

WALLPAPER PRIMER
FOR NON-POROUS SURFACES



DATA SHEET UPDATED 23/09/2024

Product information

An adhesion-promoting primer/sizer for non-porous surfaces.

- + Dries with a permanent tack
- + Water resistant
- + Low odor, no spatter
- + High yield
- + Non-flammable
- + Penetrates up to 3 cm into the support consolidating
- + Very Low V.O.C. (Volatile Organic Compounds)



Recommended uses

- Application over non-porous or sealed surfaces
- The white color makes it easy to apply wall paints.

Coverage

Approximately 107 square feet per part, depending on the porosity of the substrate.

Application instructions

Surface preparation

Surface must be free from grease and all residues, dry, smooth and structurally sound. Repair all unsound surfaces. Clean ceramic tile, paneling, glass and sealed surfaces with isopropyl alcohol. For best results, lightly sand or abrade all glossy or sealed surfaces before applying. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier. After the required surface preparation is completed, it is critical to test the surface to ensure compatibility. Select a small, inconspicuous area of the surface for testing and apply the primer or adhesive as specified. Inspect the test area after 24 hours before proceeding with the installation of wallcovering.

Product preparation

The product is ready to use.
The product retains high yield.

Application

Use only when the room temperature is above 60°F(16°C). Apply at recommended spread rate using roller or spraying system. Do not overspread.

PRIMER STO-R

ADHESION PROMOTING

WALLPAPER PRIMER FOR NON-POROUS SURFACES



DATA SHEET UPDATED 23/09/2024

Cleaning

Before the primer dries, remove any excess with clean water. Brushes and rollers should be cleaned immediately after use with a mild soap and clean, warm water.

Technical product data

Base	Acrylic water-based
Appearance and color	White liquid
PH	6.5-7.0
Viscosity	5000 cps
VOC	<2 µg/m ³
Solids percentage	50%
Customs code	3209 1000
Application temperature	+41°F- +104°F (+5°C-+40°C)
Drying Time	3/4 hours
Non-Flammable product	
Keep free from frost	

Warning

Do not apply to porous surfaces. Not recommended for direct application over oil-based primers. Protect from frost

Storage

The product is guaranteed in its original packaging, in standard conditions +41°F- +95°F (+5 °C to + 35 °C), for 24 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

Disclaimer

If you scrape, sand, or remove old paint, you may release lead dust. Keep out of reach of children. Dispose of leftovers in special containers for building materials. The information contained in the data-sheet is the result of our many years of experience but is only indicative. Therefore, those who want to use it are obliged to assess whether the product is suitable for use and take responsibility for its use.