



# PRIMER STO-SP

## TRANSPARENT - SANITIZING WALLPAPER PRIMER



DATA SHEET UPDATED 16/10/2024

### Product information

Acrylic water-based primer for walls and floors, specifically designed for damp surfaces prone to fungi and mold. It serves as a bonding agent, ideal for preparing surfaces before the direct installation of flooring and wall coverings on compatible substrates.

- + Exceptional coverage
- + Easy to apply
- + Outstanding coverage
- + Water-based, solvent-free
- + Ideal in preparations of areas that need to be leveled
- + Agglomerate the residual powder
- + Seals the pores of the mortar, improves the fluidity and workability of self-leveling compounds
- + Create powerful bonding bridges
- + High yield
- + Non-flammable
- + Penetrates up to 3 cm into the support consolidating
- + Very Low V.O.C. (Volatile Organic Compounds)



### Recommended uses

- Restoring old walls.
- Protecting and preventing fungi and molds on wet walls.
- PRIMER STO-SP prepares the wall surface before applying wall coverings and paints.

### Coverage

Approximately 75 square feet per part, depending on the porosity of the substrate.

### Application instructions

#### Product preparation

The product is ready to use.

The application substrate must meet the compatibility requirements of the Primer. In particular, they must be clean, free of structural defects, stationary, permanently dry and free of release agents. In the case of cementitious substrates, any retention must be removed by special machines.

#### Application

Shake well before use. Apply PRIMER STO-SP to walls or floors using a roller or brush, ensuring that no puddles form. The product typically dries within 3 to 4 hours at a temperature of 68-73°F (20-23°C), although drying time can vary depending on environmental temperature and conditions. On particularly porous surfaces, a second coat may be necessary. Drying time is influenced by the relative humidity and absorbency of the

# PRIMER STO-SP

TRANSPARENT - SANITIZING  
TRANSPARENT WALLPAPER  
PRIMER



DATA SHEET UPDATED 16/10/2024

substrate; it will be shorter in higher temperatures and lower humidity, but longer in lower temperatures, higher humidity, and with non-absorbent substrates.

#### Cleaning

Clean possible spills with a damp sponge.

THE PRODUCT DOES NOT STAIN

#### Technical product data

|                         |                      |
|-------------------------|----------------------|
| Base                    | Acrylic water based  |
| Appearance and color    | White liquid         |
| PH                      | 6.5                  |
| Viscosity               | 500-700 cps          |
| VOC                     | <2 µg/m <sup>3</sup> |
| Solids percentage       | 50 %                 |
| Customs code            | 3209 1000            |
| Application temperature | +41°F-+104°F         |
| Drying Time             | 48 hours             |
| Non-Flammable product   |                      |
| Keep free from frost    |                      |

#### Warning

Do not apply on non-absorbent substrates (glass, ceramic, laminates). Protect from frost. Do not install floor coverings at temperatures below 59°F (15 °C) and above 122°F (50 °C) or at a relative humidity above 75 %. Do not mix PRIMER STO-SP with other primers. Do not apply to wood substrates. Do not add additional water.

#### Storage

The product is guaranteed in its original packaging, in standard conditions +41°F to + 95°F (+5 °C to + 35 °C), for 24 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

#### Disclaimer

PRIMER STO-SP is free of solvents, lead or other heavy metals and is a suitable alternative to products containing solvents. No special safety precautions are necessary when working with the product, however personal protective equipment should be used as rubber gloves for industrial use, goggles and a dust mask. The risk of medium or long-term

# PRIMER STO-SP

---

TRANSPARENT - SANITIZING

TRANSPARENT WALLPAPER

PRIMER



DATA SHEET UPDATED 16/10/2024

---

release of appreciable concentrations of volatile organic chemicals (VOCs) into ambient air is insignificant. However, ensure adequate ventilation during and after application and drying. Avoid eating, drinking or smoking while working with the product.

Protect eyes and skin. In case of contact with eyes or skin rinse immediately with plenty of water. After contact also consult a doctor.

The information contained in the data-sheet, despite being the result of our long experience, are only indicative. Therefore, those who intend to use it must assess whether the product is suitable for the application and assume responsibility for the use.

---