



# TEXRECO CN100

---

## CLEAR STRIPPABLE WALLPAPER ADHESIVE HEAVY DUTY



DATA SHEET UPDATED 22/05/2024

---

### Product information

Natural Starch paste ready-to-use adhesive for all types of wallpaper, including commercial weight wallcoverings.

- + Exceptional adhesive strength
- + Does not stain
- + High yield
- + Very Low V.O.C. (Volatile Organic Compounds)



---

### Recommended uses

- Paper backed vinyl wall coverings and non-woven wall coverings
- Contract wall coverings. Ideal height: from 53 cm to 160 cm
- Expanded wall coverings
- Non-woven wall coverings
- Fiberglass wall coverings
- Textile wall coverings

---

### Coverage

Approximately 350 square feet per gallon, depending on the porosity of the substrate.

---

### Application instructions

#### Surface preparation

All surfaces must be dry, absorbent, strong, and free of dust, paints, or oils. Any cracks or holes in the wall must be filled with our extra-light stucco GLASTER. We always recommend using our Primer STO-B if there are mildew stains on the wall, our Primer STO-R like promoter for non-porous surfaces and our Primer STO-SP to fix and prevent mouldings on the walls.

#### Product preparation

TEXRECO CN100 is a ready-to-use product however, when necessary, dilute it with clean water up to a maximum of 5/10%.

#### Application

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

#### Cleaning

Clean possible spills with a damp sponge.

THE PRODUCT DOES NOT STAIN

# TEXRECO CN100

CLEAR STRIPPABLE WALLPAPER  
ADHESIVE  
HEAVY DUTY



DATA SHEET UPDATED 22/05/2024

## Technical product data

Base	Natural Resin
Appearance and colour	White cream
PH	6.5
Viscosity	60000-80000 cps
VOC	<2 µg/m <sup>3</sup>
Solids percentage	> 35%
Customs code	3505 2010
Application temperature	+5°C +40°C
Waiting Time	0-10 min
Open Time	20-30 min
Drying Time	48 hours
Non-Flammable product	
Keep free from frost	

## Warning

TEXRECO CN100 is not suitable on non-absorbent substrates, humid walls with mold or on surfaces not perfectly prepared. Spillage of the adhesive should be removed immediately with a damp sponge. Keep out of reach of children and pets. Discharge the waste in special containers for building materials.

## Storage

The product is guaranteed in its original packaging, in standard conditions (+5 °C a +35 °C or +41 °F to +95 °F), for 24 months from the date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

## Disclaimer

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.