



TEXRECO CT80

CLEAR WALLPAPER ADHESIVE
MEDIUM DUTY



DATA SHEET UPDATED 22/05/2024

Product information

Natural resin-based paste ready-to-use adhesive for all types of wallpapers, including fiberglass and commercial weight wallcoverings.

- + Exceptional adhesive strength
- + Does not stain
- + High yield
- + Very Low V.O.C. (Volatile Organic Compounds)



Recommended uses

- Heavy vinyl wallpapers with paper or non-woven backing
- Heavyweight, paintable and non-paintable non-woven wall coverings
- Expanded wall coverings
- Fiberglass wall coverings, any thickness
- Thermal and sound absorbing wall coverings

Coverage

Approximately 350 square feet per gallon, depending on the porosity of the substrate.

Application instructions

Surface preparation

All surfaces must be dry, absorbent, strong, and free of dust, paints, or oils. Any cracks or holes in the wall must be filled with our extra-light stucco GLASTER. We always recommend using our Primer STO-B if there are mildew stains on the wall, our Primer STO-R like promoter for non-porous surfaces and our Primer STO-SP to fix and prevent mouldings on the walls.

Product preparation

TEXRECO CT80 is a ready-to-use product however, when necessary, dilute it with clean water up to a maximum of 5/10%.

Application

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

Cleaning

Clean possible spills with a damp sponge.

THE PRODUCT DOES NOT STAIN

TEXRECO CT80

CLEAR WALLPAPER ADHESIVE
MEDIUM DUTY



DATA SHEET UPDATED 22/05/2024

Technical product data

| Base | Natural Resin |
|-------------------------|------------------------|
| Appearance and colour | White cream |
| PH | 6.5 |
| Viscosity | 40000-50000 cps |
| VOC | < 2 µg/ m ³ |
| Solids percentage | > 35% |
| Customs code | 3505 2010 |
| Application temperature | +5°C +40°C |
| Waiting Time | 0-10 min |
| Open Time | 20-30 min |
| Drying Time | 48 hours |
| Non-Flammable product | |
| Keep free from frost | |

Warning

TEXRECO CT80 is not suitable on non-absorbent substrates, humid walls with mold or on surfaces not perfectly prepared. Spillage of the adhesive should be removed immediately with a damp sponge. Keep out of reach of children and pets. Discharge the waste in special containers for building materials.

Storage

The product is guaranteed in its original packaging, in standard conditions (+5 °C a +35 °C or +41 °F to +95 °F), for 24 months from the date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

Disclaimer

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.