



TEXRECO X100

TRANSPARENT WALLPAPER ADHESIVE EXTREME DUTY



DATA SHEET UPDATED 22/05/2024

Product information

Transparent ready-mix adhesive for all types of wallcoverings. Suitable for absorbent and non-absorbent surfaces.

- + Extra Clear
- + Exceptional adhesive strength
- + Does not stain
- + High yield
- + Very Low V.O.C. (Volatile Organic Compounds)



Recommended uses

- Vinyl contract wall coverings with fabric or non-woven backing with a weight up to 1 kg/m²
- Fiberglass wall coverings
- Paintable wall coverings
- Wallcoverings with cotton fabric support
- Difficult application

Coverage

Approximately 200 square feet per gallon, depending on the porosity of the substrate.

Application instructions

Surface preparation

All surfaces must be dry, absorbent, strong, and free of dust, paints, or oils. Any cracks or holes in the wall must be filled with our extra-light stucco GLASTER. We always recommend using our Primer STO-B if there are mildew stains on the wall, our Primer STO-R like promoter for non-porous surfaces and our Primer STO-SP to fix and prevent mouldings on the walls.

Product preparation

TEXRECO X100 is a ready-to-use product however, when necessary, dilute it with clean water up to a maximum of 5/10%.

Application

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

Cleaning

Clean possible spills with a damp sponge.

THE PRODUCT DOES NOT STAIN

TEXRECO X100

TRANSPARENT WALLPAPER

ADHESIVE

EXTREME DUTY



DATA SHEET UPDATED 22/05/2024

Technical product data

Base	Starch
Appearance and colour	White cream
PH	6.5
Viscosity	65000-75000 cps
VOC	< 2 µg/m ³
Solids percentage	> 40%
Customs code	3505 2010
Application temperature	+5°C +40°C
Waiting Time	0-10 min
Open Time	15-20 min
Drying Time	48 hours
Non-Flammable product	
Keep free from frost	

Warning

TEXRECO X100 is not suitable on imperfect prepared substrates or humid walls. Spillage of the adhesive should be removed immediately with a damp sponge.
Keep out of reach of children and pets. Discharge the waste in special containers for building materials.

Storage

The product is guaranteed in its original packaging, in standard conditions (+5 °C a +35 °C or +41 °F to +95 °F), for 24 months from the date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

Disclaimer

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.