



VICEVERSA PLASTER



ACRYLIC WATERPROOFING MEMBRANE

UPDATED DATA SHEET 30/09/2026

Product information

One-component, ready-to-use acrylic waterproofing coating for wet and humid areas, both indoors and outdoors.

Ideal for waterproofing bathrooms, showers, balconies, terraces and flat roofs. It forms a continuous, elastic and durable membrane suitable for foot traffic.

- + Outstanding performance
- + High coverage
- + Low VOC (volatile organic compounds)
- + Suitable for foot traffic
- + Elastic

Recommended Uses

- Waterproofing of substrates before laying tiles in bathrooms, showers and wet rooms.
- Waterproofing of balconies and terraces.
- Waterproofing of flat roofs.

Coverage

Approx. 1500 g/m² for 1.5 mm thickness.

Application Instructions

Preparation of the bottom

All subfloors must be dry, absorbent, durable and free of dust, paints or oils. Any cracks should be sealed with our two-component epoxy EPOXY ECO adhesive.

In the case of uneven surfaces, we recommend the application of a powdered cementitious skim coat such as our SELF LEVEL FLOORING from the Supremo line, or the ready-to-use TILECOAT skim coat.

For the consolidation and cleaning of the substrate, the use of our fixative PRIMER SP is recommended.

Product preparation

Ready-to-use product. If necessary, dilute with up to 5% clean water.

Product Application

Apply with a roller or brush, creating a uniform thickness of about 1.5 mm.

Cleaning

Clean the tools with water immediately after use.



VICEVERSA PLASTER



ACRYLIC WATERPROOFING MEMBRANE

UPDATED DATA SHEET 30/09/2026

Contraindications

Do not apply to non-absorbent substrates. In the case of ceramic tiles, it is advisable to sand them to make them porous. Before proceeding with the installation, apply a coat of PRIMER AC diluted 1:5. HE FEARS THE COLD.

Product Technical Data

Basic	Acrylic
Physical appearance	Creamy paste
Colors	White, Grey, Red, Transparent
PH	6.5
Viscosity	2500cps
Percentage of solids	Approx. 70%
Customs code	3506 9100
Application temperature	+5°C +40°C
Drying time	6/8 hours
Adhesion to the substrate (EN 1542)	2.2 MPa
Vapour permeability (EN ISO 7783)	Class I – Sd 0.8 m
Capillary absorption (EN 1062-3)	$W = 0.07 \text{ kg/m}^2 \cdot h^{0.5}$
Water tightness (EN 14891)	Compliant
Non-flammable	

Final provisions

Keep out of reach of children and pets. Dump waste into appropriate containers for building materials.

Storing

The product is guaranteed in the original packaging, under standard conditions (+5°C + 35°C), for 24 months from the date of production. It is



VICEVERSA PLASTER

ACRYLIC WATERPROOFING
MEMBRANE



UPDATED DATA SHEET 30/09/2026

important to store the product in a dry place away from heat sources and direct sunlight.

Warnings

The information described in this Technical Data Sheet is based on our decades of experience but is indicative. Therefore, the user must assess whether the product is suitable for its specific application and take responsibility for its use.