



VICEVERSA PLASTER

READY-TO-USE WATERPROOFING MEMBRANE



UPDATED TECHNICAL DATA SHEET 14/10/2026

Product information

Ready-to-use waterproofing membrane designed to protect surfaces from water in wet and damp areas, both indoors and outdoors.

Ideal for bathrooms, showers, balconies, terraces, and flat roofs, it creates a flexible, durable barrier suitable for pedestrian traffic. It provides excellent adhesion and high coverage.

- + High waterproofing performance
- + High coverage
- + Low VOC emissions
- + Suitable for pedestrian traffic
- + High flexibility

Recommended uses

- Waterproofing substrates before tile installation in bathrooms, showers, and wet areas
- Waterproofing balconies and terraces
- Waterproofing flat roofs

Coverage

Approximately 1,500 g/m² at a thickness of 1.5 mm.

Application instructions

Substrate preparation

Substrates must be dry, absorbent, sound, clean, and free from dust, paint, oil, and other contaminants.

Seal any cracks using the two-component epoxy adhesive EPOXY ECO.

For uneven surfaces, we recommend applying a cement-based powder leveling compound, such as SELF LEVEL FLOORING from the Suprimo line, or a ready-to-use skim coat, such as TILECOAT.

To consolidate and prepare the substrate, we recommend applying PRIMER SP.

Product preparation

The product is ready to use. If necessary, dilute with up to 5% clean water.

Product Application

Apply with a roller or brush to achieve a uniform thickness of approximately 1.5 mm.

Cleaning

Clean tools with water immediately after use..

ACM Italy S.r.l.
Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan), Italy
+39 02 90361148 | info@acm-italy.com
www.acm-italy.com



VICEVERSA PLASTER

READY-TO-USE WATERPROOFING MEMBRANE



UPDATED TECHNICAL DATA SHEET 14/10/2026

Technical Data	Base	Acrylic
	Physical appearance	Creamy paste
	Colors	White, grey, red, transparent
	pH	6.5
	Viscosity	2,500 cP
	Solid content	Approx. 70%
	Customs code	3506 9100
	Application temperature	+5°C to +40°C (41°F to 104°F)
	Drying time	6–8 hours
	Flammability	Non-flammable

Contraindications

Do not apply directly to non-absorbent substrates.

When applying over ceramic tiles, sand or mechanically abrade the surface to make it porous. Before application, apply one coat of PRIMER AC diluted 1:5.

Protect from freezing.

Warning

Keep out of reach of children and pets.

Dispose of product waste and empty containers in accordance with applicable local regulations for construction materials.

Storage

The product has a shelf life of 24 months from the date of manufacture when stored in its unopened original packaging under standard conditions at temperatures between +5°C and +35°C (41°F and 95°F).

Store in a dry place, away from heat sources and direct sunlight, to preserve the product's properties and shelf life. Protect from freezing.



VICEVERSA PLASTER

READY-TO-USE WATERPROOFING MEMBRANE



UPDATED TECHNICAL DATA SHEET 14/10/2026

Disclaimer

The information provided in this Technical Data Sheet is based on our long-standing experience but is intended as a guideline. Therefore, the user must assess whether the product is suitable for their specific application and takes full responsibility for its use.