



VICEVERSA TILECOAT

PROFESSIONAL FILLER AND SURFACING COMPOUND FOR TILES



UPDATED DATA SHEET 11/09/2025

Product information

Universal filler and surfacing compound suitable for indoor and outdoor use, ready to apply. It offers excellent adhesion to tiles, low shrinkage, easy sanding, and resistance in humid environments.

- + Ready to use
- + Strong adhesion to tiles
- + Crack-free and low shrinkage
- + Suitable for humid environments
- + Easy to sand

Suggested Applications

- Renovating tiled surfaces without removing ceramics
- Smoothing and leveling concrete or old textured coatings
- Can be painted over with any water-based paint or enamel
- Filling holes and cracks in indoor and outdoor settings
- Filling joints between tiles

Product yield

Approx. 1–1.2 kg/m²

Application Guidelines

Substrate preparation

All substrates must be dry, solid, and free of dust, paint, or oils. If necessary, protect any exposed metal parts with an anti-corrosive and/or insulating product.

Product preparation

Ready to use.

Product Application

Apply the product using a trowel or smoothing tool.

Cleaning

Clean tools with water while the product is still fresh. Once dried, remove mechanically.

Product Technical Data

Base	Water-based polymers
Physical appearance	Dense cream-colored paste
pH	Neutral
Density	1.2 g/cm ³

ACM Italy S.r.l.

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan), Italy

+39 02 90361148 | info@acm-italy.com

www.acm-italy.com



VICEVERSA TILECOAT

PROFESSIONAL FILLER AND SURFACING COMPOUND FOR TILES



UPDATED DATA SHEET 11/09/2025

Solid content	Approx. 85%
Customs code	3506 9100
Application temperature	+10°C to +35°C
Waiting time	None
Open time	Approx. 40–60 minutes
Drying time	12 h per mm

Contraindications

Do not apply at temperatures below +5°C.
Recommended application temperature: between +10°C and +35°C.

Final provisions

Keep out of reach of children and pets.
Dispose of waste in designated construction material containers.

Preservation

The product, in its original packaging and under standard conditions (+5°C / +35°C | 41°F / 95°F), is guaranteed for 12 months from the date of manufacture.
It is essential to store it in a dry place, away from sources of heat and direct sunlight, to preserve its properties and shelf life.

Warnings

The information provided in this Technical Data Sheet is based on our long-standing experience but is intended as a guideline. Therefore, the user must assess whether the product is suitable for their specific application and takes full responsibility for its use.