



# VICEVERSA TILECOAT

READY-TO-USE FILLING AND  
LEVELLING COMPOUND



UPDATED DATA SHEET 19/05/2025

## Product information

Universal Lightweight Polymer-Based Levelling and Filling Compound for Interior and Exterior Applications

- + Solvent-free
- + Low shrinkage
- + No retraction
- + Excellent adhesion
- + Ready to use
- + Easy to sand

## Suggested Applications

- To renovate tiled surfaces without removing the ceramic tiles
- To skim and level concrete surfaces or old plastic coatings
- Paintable with any type of water-based paint or enamel
- For filling holes and cracks in both interior and exterior settings

## Product yield

Approx. 1–1.2 kg/m<sup>2</sup>

## Application Guidelines

### Substrate preparation

All substrates must be dry, solid, and free of dust, paint, or oils. If necessary, protect any exposed metal parts with an anti-corrosive and/or insulating product.

### Product preparation

Ready to use.

### Product Application

Apply the product using a trowel or smoothing tool.

### Cleaning

Clean tools with water while the product is still fresh. Once dried, remove mechanically.

## Product Technical Data

Base	Water-based polymers
Physical appearance	Dense cream-colored paste
pH	Neutral
Density	1.2 g/cm <sup>3</sup>



# VICEVERSA TILECOAT



## READY-TO-USE FILLING AND LEVELLING COMPOUND

UPDATED DATA SHEET 19/05/2025

Solid content	Approx. 85%
Customs code	3506 9100
Application temperature	+10°C to +35°C
Waiting time	None
Open time	Approx. 40–60 minutes
Drying time	12 h per mm

### Contraindications

Do not apply at temperatures below +5°C.  
Recommended application temperature: between +10°C and +35°C.

### Final provisions

Keep out of reach of children and pets.  
Dispose of waste in designated construction material containers.

### Preservation

The product, in its original packaging and under standard conditions (+5°C / +35°C | 41°F / 95°F), is guaranteed for 12 months from the date of manufacture.  
It is essential to store it in a dry place, away from sources of heat and direct sunlight, to preserve its properties and shelf life.

### Warnings

The information provided in this Technical Data Sheet is based on our long-standing experience but is intended as a guideline. Therefore, the user must assess whether the product is suitable for their specific application and takes full responsibility for its use.