



VICEVERSA TILECOAT



PROFESSIONAL FILLER AND SURFACING COMPOUND, INCLUDING FOR TILED SURFACES

UPDATED DATA SHEET 14/10/2026

Product information

Ready-to-use universal filler and surfacing compound suitable for interior and exterior applications. It provides excellent adhesion to tiles, low shrinkage, easy sanding, and excellent performance in humid environments.

- + Ready to use
- + Strong adhesion to tiles
- + Crack-resistant and low-shrinkage formulation
- + Suitable for humid environments
- + Easy to sand

Recommended uses

- Renovating tiled surfaces without removing the existing tiles
- Smoothing and leveling concrete surfaces or existing textured coatings
- Overcoating with water-based paints or enamels
- Filling holes and cracks in interior and exterior applications
- Filling tile joints

Coverage

Approx. 1–1.2 kg/m²

Application instructions

Substrate preparation

All substrates must be dry, sound, and free from dust, paint, oil, and other contaminants. If necessary, protect any exposed metal components with a suitable anti-corrosion and/or insulating product.

Product preparation

Ready to use.

Product Application

Apply the product using a trowel or suitable smoothing tool.

Cleaning

Clean tools with water while the product is still wet. Once dry, the product must be removed mechanically.

Technical Data

Base	Water-based polymers
Physical appearance	Thick, cream-colored paste
pH	Neutral

ACM Italy S.r.l.

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan), Italy

+39 02 90361148 | info@acm-italy.com

www.acm-italy.com



VICEVERSA TILECOAT

PROFESSIONAL FILLER
AND SURFACING
COMPOUND, INCLUDING
FOR TILED SURFACES



UPDATED DATA SHEET 14/10/2026

Density	1.2 g/cm ³
Solid content	Approx. 85%
Customs code	3506 9100
Application temperature	+10°C to +35°C
Waiting time	None
Open time	Approx. 40–60 minutes
Drying time	12 h per mm

Contraindications	Do not apply at temperatures below +5°C. The recommended application temperature is between +10°C and +35°C.
--------------------------	--

Warning	Keep out of reach of children and pets. Dispose of waste in designated construction waste containers.
----------------	---

Storage	When stored in its original packaging under standard conditions, between +5°C and +35°C (41°F and 95°F), the product is guaranteed for 12 months from the date of manufacture. Store in a dry place, away from heat sources and direct sunlight, to preserve its properties and shelf life.
----------------	---

Disclaimer	The information provided in this Technical Data Sheet is based on our extensive experience and is intended as a general guideline. The user must determine whether the product is suitable for the intended application and assume full responsibility for its use.
-------------------	---