



VICEVERSA WET SYSTEM OUTDOOR



COMPLETE PROFESSIONAL
SYSTEM FOR OUTDOOR
WALLCOVERING INSTALLATION.

UPDATED DATA SHEET 19/02/2026

Product information

VICEVERSA WET SYSTEM OUTDOOR is a complete system designed for the application of technical wallpapers and decorative wallcoverings on outdoor surfaces exposed to rain, humidity, thermal shock, and UV rays. Ideal for façades, loggias, courtyards, and exterior walls.

The system includes:

- VICEVERSA PRIMER+ PLUS – sanitizing and consolidating primer
- VICEVERSA SPECIAL MS – flexible one-component MS polymer adhesive for outdoor use
- VICEVERSA COAT MIRROR – ultra-glossy epoxy protective finish
- VICEVERSA DIAMOND – structural multipurpose adhesive/sealant

PRIMER+ PLUS

Description:

Anti-mold, antibacterial, and sanitizing primer based on acrylic resins, enriched with our exclusive thymol-based gel, THYMOLGEL.

Suitable for:

- Sanitizing old and new substrates
- Preventing mold and mildew
- Consolidating wall surfaces prior to paint, wallpaper, vinyl, and LVT coverings

Technical features:

- + Ready to use or dilutable 1:1 with water
- + Water-based
- + Gel consistency, non-drip
- + Low VOC
- + Contains natural thymol (sanitizing agent)

Application:

Apply on dry walls or floors using brush or roller. Drying time: 3–4 h at 20–23°C.

Consumption: 100–200 g/m²

Packaging: 1 L bottle | Code 30196-N

Storage: 24 months in original packaging at +5/+35°C



VICEVERSA WET SYSTEM OUTDOOR



COMPLETE PROFESSIONAL
SYSTEM FOR OUTDOOR
WALLCOVERING INSTALLATION.

UPDATED DATA SHEET 19/02/2026

VICEVERSA SPECIAL MS

Description:

Single-component adhesive based on modified silane polymers (MS polymer), elastic, weather and UV resistant.

Suitable for:

- Application of fiberglass and technical wallcoverings on exterior walls
- Absorbent and non-absorbent substrates (plaster, concrete, ceramic, metal, EPS)

Features:

- + Flexible and elastic
- + Excellent adhesion under critical conditions
- + Waterproof and UV-resistant
- + Solvent-free, low VOC

Application:

Apply evenly with notched trowel or roller. Open time: approx. 30 minutes.

Consumption: 250–350 g/m²

Packaging: 5 kg bucket | Code 30061

Storage: 12 months in original packaging at +5/+35°C

VICEVERSA COAT MIRROR

Description:

Two-component transparent epoxy protective finish, extra glossy. Designed for coating wall and resin flooring surfaces, providing high resistance to scratches, wear, and atmospheric agents.

Suitable for:

- Outdoor wallcoverings
- Resin floors
- Self-leveling coatings

Features:

- + Extra glossy, transparent finish
- + Does not alter substrate color
- + Non-yellowing, solvent-free

Preparation:



VICEVERSA WET SYSTEM OUTDOOR



COMPLETE PROFESSIONAL
SYSTEM FOR OUTDOOR
WALLCOVERING INSTALLATION.

UPDATED DATA SHEET 19/02/2026

Mix part A and part B in a 100:60 weight ratio (e.g., 1 kg A + 0.6 kg B) until homogeneous.

Application:

Pour and spread with smooth or notched trowel. Spray PU COAT DILUENT within 5–10 minutes to eliminate air bubbles.

Consumption:

- 2.2 kg/m² for 2 mm thickness
- 1.2 kg/m² for 1 mm thickness

Packaging: Kit A+B

Storage: 12 months at +5/+35°C

VICEVERSA DIAMOND

Description:

Sealant/adhesive based on modified silane polymers. Strong initial grip and low elastic modulus. Suitable for structural bonding, even in outdoor conditions.

Suitable for:

- Structural joints and bonding
- Metal, glass, plastic, EPS, concrete

Technical features:

- + Ready to use in cartridge
- + High initial tack
- + Low VOC, solvent-free

Application:

Apply directly from cartridge using a manual gun. Coverage: approx. 15 linear meters per cartridge.

Cleaning:

Clean tools with nitro thinner before curing.

Packaging:

300 ml cartridge | Code 30128T (transparent)

Storage: 12 months in original packaging at +5/+35 °C